

## HERBY DERBY Western Montana Fair 2009

### Prep Rules

1. All Regular Western Montana Fair Demolition Derby car building rules apply if they are not listed here in the small car rules!
2. Any 2, 3 or 4 cylinder passenger cars or small trucks are eligible. No all wheel drive, rotary, super-charged or turbo-charged cars are allowed. 6 cylinder front wheel drive cars within the approved wheelbase are allowed.
3. Maximum 104" wheelbase. (Camaros and Fairmonts are over allowed size)
4. Cars and trucks must have minimum 6" channel on both doors.
5. A minimum of 2 hood pins MUST be installed to hold the hood closed. Option: You may install up to 4, 3/4" length bolts/threaded rods to hold the hood closed. 2 in the core support bolt holes and 2 in the middle or rear portion of the hood.
6. Stock gas tanks may remain in stock locations if they are mounted in front of rear suspension but they must have a minimum of 2 additional metal straps or chains holding them in place--these are besides the stock ones. Filler cap must be moved inside trunk per tech discretion. Option: gas tanks may be moved inside the car per WMF regular car rules.
7. Battery may remain in stock location securely fastened. Option: moved inside of the car as per WMF regular car rules
8. Two (2) clean cut 8" minimum diameter fire holes must be cut in the hood (one on each side of the engine) Exception: If both front wheel wells are removed no holes in hood are required
9. Any stock-type mag wheel may be used.
10. Drivers door may be welded